

Component Parameter Test Instruments

A. TH2840 Series Precision LCR Meter

Features

- The test speed is as high as 1000 times/s (>10kHz), without relay action time
- Test level up to 20Vrms
- The bias voltage is built-in $\pm 40V/\pm 100mA/2A$
- Up to 288 test pins (only TH2840NX)
- Industry-friendly user experience: Linux bottom layer, built-in help file
- 10.1 inch 1280×800 capacitive touch screen
- Graphical pin association setting page, so that wiring is no longer a problem
- Lk setting does not need to input the leakage inductance pin, which is more intuitive
- Enhanced balance scanning function, from 5 points to 10 points
- Range switching adopts electronic switch, fast speed, long life, no noise
- Optional LCR function
- Approximately 100M setting file storage space in the machine, and massive U disk setting file storage capacity
- Provide host computer to support early model file format conversion to ensure compatibility

Applications

- **Passive component:**
Impedance parameter estimation and performance analysis of capacitor, inductor, magnetic core, resistor, piezoelectric devices, transformers, chip components and network components
- **Semiconductor component**
Parasitic parameter test and analysis of LED driver integrated circuit
C-VDC features of varactors
Parasitic parameter analysis of transistors or integrated circuit
- **Other components**
Impedance assessment of printed circuit boards, relays, switches, cables, batteries



Standard	RS232 <input type="checkbox"/>	USB HOST <input type="checkbox"/>	USB DEVICE <input type="checkbox"/>
	HANDLER <input type="checkbox"/>	LAN <input type="checkbox"/>	EXTERNAL DCI <input type="checkbox"/>

Dimension: 430mm(W)x177mm(H)x265mm(D)

Weight: 11kg

- **Dielectric material**
Dielectric constant and loss angle evaluation of plastics, ceramics and other materials
- **Magnetic materials**
Magnetic permeability and loss angle assessment of ferrite, amorphous body and other magnetic materials
- **Semiconductor materials**
Dielectric constant, electrical conductivity and C-V characteristics of semiconductor materials
- **Liquid crystal cell**
Dielectric constant, elastic constant and C-V characteristics of liquid crystal cell

Specifications

Model	TH2840A	TH2840B	
Display	Display	10.1" Touch Screen	
	Ratio	16:9	
	Resolution	1280×RGB×800	
Parameter	Test Mode	Four Parameter Selectable	
	AC	Cp/Cs、Lp/Ls、Rp/Rs、 Z 、 Y 、R、X、G、B、 θ 、D、Q、 V_{AC} 、 I_{AC}	
	DC	R_{DC} 、 V_{DC} 、 I_{DC}	
Frequency	Range	20Hz-500kHz	
	Accuracy	0.01%	
	Resolution	0.1mHz	(20.0000Hz-99.9999Hz)
		1mHz	(100.000Hz-999.999Hz)
		10mHz	(1.00000kHz-9.99999kHz)
		100mHz	(10.0000kHz-99.9999kHz)
		1Hz	(100.000kHz-999.999kHz)
10Hz	(1.00000MHz-2.00000MHz)		
AC test signal mode	Rated value (ALC OFF)	Set the voltage as the Hcur voltage when the test terminal is open Set the current to be the current flowing from Hcur when the test terminal is	
	Constant value (ALC ON)	Keep the voltage on the DUT the same as the set value Keep the current on the DUT the same as the set value	

Component Parameter Test Instruments

A. TH2840 Series Precision LCR Meter

Test Level	AC Voltage	5mVrms-20Vrms	F≤1MHz 5mVrms-20Vrms F>1MHz 5mVrms-15Vrms
	Accuracy	± (10%×Set Value+2mV) (AC less than 2Vrms) ± (10%×Set Value+5mV) (AC>2Vrms)	
	Resolution	1mVrms (5mVrms-0.2Vrms)	
		1mVrms (0.2Vrms-0.5Vrms)	
		1mVrms (0.5Vrms-1Vrms)	
		10mVrms (1Vrms-2Vrms)	
		10mVrms (2Vrms-5Vrms)	
10mVrms (5Vrms-10Vrms)			
10mVrms (10Vrms-20Vrms)			
AC Current	50 μ Arms-100mArms		
Resolution(100 Ω Internal Resistance)	10 μ Arms (50 μ Arms-2mArms)		
	10 μ Arms (2mArms-5mArms)		
	10 μ Arms (5mArms-10mArms)		
	100 μ Arms (10mArms-20mArms)		
	100 μ Arms (20mArms-50mArms)		
100 μ Arms (50mArms-100mArms)			
R _{DC} Test	Voltage	100mV-20V	
	Resolution	1mV (0V-1V)	
		10mV (1V-20V)	
	Current	0mA-100mA	
Resolution	10 μ A (0mA-10mA)		
	100 μ A (10mA-100mA)		
DC Bias	Voltage	0V-±40V	
	Accuracy	AC≤2V 1%×Set Value+5mV	
		AC>2V 2%×Set Value+8mV	
	Resolution	1mV (0V-1V)	
		10mV (±1V- ±40V)	
Current	0mA-±100mA		
Resolution	10 μ A (0mA-10mA)		
	100 μ A (10mA-100mA)		
Built-in current source	Current	0mA-2A	
	Accuracy	I>5mA ± (2%×Set Value+2mA)	
	Resolution	1mA	
Test terminal configuration	Four Terminal Pair		
Test cable length	0m		
Output impedance	30 Ω, ±4%@1kHz 100 Ω, ±2%@1kHz		
computation	The absolute deviation from the nominal value Δ, the percentage deviation from the nominal value Δ %		
Equivalent way	Series, Parallel		
Calibration function	OPEN、SHORT、LOAD		
Measurement average	1-255		
Range selection	AUTO、HOLD		
Range configuration	LCR	100mΩ、1Ω、10Ω、20Ω、50Ω、100Ω、200Ω、500Ω、1kΩ、2kΩ、5kΩ、10kΩ、20kΩ、50kΩ、100kΩ	
	R _{DC}	1Ω、10Ω、20Ω、50Ω、100Ω、200Ω、500Ω、1kΩ、2kΩ、5kΩ、10kΩ、20kΩ、50kΩ、100kΩ	
Measuring time (ms)	Fast+: 1ms Fast: 3.3ms Middle: 90ms Slow: 220ms		
Highest accuracy	0.05% (refer to the instruction manual for details)		
Measurement display range			
Cs、Cp	0.00001pF-9.99999F		
Ls、Lp	0.00001 μ H-99.99999kH		
D	0.00001-9.99999		
Q	0.00001-99999.9		
R、Rs、Rp、X、Z、R _{DC}	0.001mΩ-99.9999MΩ		

Component Parameter Test Instruments

A. TH2840 Series Precision LCR Meter

G, B, Y	0.00001 μ s-99.9999S		
V _{DC}	$\pm 0V$ - $\pm 999.999V$		
I _{DC}	$\pm 0A$ - $\pm 999.999A$		
θ_r	-3.14159-3.14159		
θ_d	-179.999° -179.999°		
Δ %	$\pm (0.000\%-999.9\%)$		
Multi-function parameter list scan	Dots Number	201 points, average times can be set for each point, and each point can be sorted separately	
	Parameter	Test frequency, AC voltage, AC current, DC BIAS voltage, DC BIAS current (100mA), DC BIAS current (2A)	
	Trigger mode	Sequence SEQ: After a trigger, measure at all sweep points, and /EOM/INDEX will output only once Step STEP: Perform a sweep point measurement each time it is triggered, and each point outputs /EOM/INDEX, but the list sweep comparator result is only output at the last /EOM	
	Other features	1.Scan parameters and test parameters have multiple copy functions 2.Delay can be set for each scan point	
	Comparators	每Each sweep point can measure up to four test parameters, each parameter can set upper and lower limits, all test parameters are qualified, output PASS signal, otherwise output FAIL signal, no upper and lower limits are set, no judgment	
Graphic scan	Scan points	51、101、201、401、801 Optional	
	The results	The extreme value of each parameter and the sweep parameter value at the point where the cursor is located and the corresponding test parameter value	
	Scan trajectory	1-4 test parameters can be selected arbitrarily, the scanning curve can be divided into one screen, two screens, or four screens	
	Display range	Real-time automatic, locked	
	Coordinate ruler	Logarithmic, linear	
	Scan parameters	Frequency, AC voltage, AC current, DCV BIAS / DCI BIAS (100mA) / DCI BIAS (2A)	
	Trigger mode	single	Manually trigger once, and complete a scan from the start point to the end point, and the next trigger signal starts a new scan
		continuous	Infinite loop scanning from start to end
Results save	Graphics, files		
Comparators	Bin	10Bin、PASS、FAIL	
	Bin deviation setting	Deviation value, percentage deviation value, off	
	Bin mode	Tolerance, continuous	
	Bin count	0-99999	
	Discrimination	Up to four parameter limit ranges can be set for each file. The corresponding file number is displayed within the setting range of the four test parameter results. If the maximum file number range is exceeded, FAIL is displayed. The test parameters without the upper and lower limits are automatically ignored.	
	PASS/FAIL indication	Meet Bin1-10, the PASS light on the front panel is on, otherwise the FAIL light	
Data cache	201 measurement results can be read in batches		
Store call	Inside	About 100M non-volatile memory test setting file	
	External USB	Test setting file, screenshot graph, record file	
Keyboard lock	The front panel keys can be locked, other functions to be expanded		
Interface	USB HOST	2 USB HOST ports, can connect mouse and keyboard at the same time, only one U disk can be used at the same time	
	USB DEVICE	Universal serial bus socket, small type B (4 contact positions); compatible with USB TMC-USB488 and USB2.0, the female connector is used to connect an external controller.	
	LAN	10/100M Ethernet adaptive	
	HANDLER	Used for Bin signal output	
	External DC BIAS control	Support TH1778A	
	RS232C	Standard 9-pin, cross	
	RS485	Can accept modification or external RS232 to RS485 module	
Power-on warm-up time	60 Minutes		
Input voltage	100-120VAC/198-242VAC Option, 47-63Hz		
Power consumption	More than 130VA		
Size (WxHxD) mm ³	430x177x265		
Weight (kg)	11kg		